



# HYCOM DATASHEET

PRESSURIZING TOOL FOR AIRCRAFT MAINTENANCE  
MODEL HPT

## IDEAL FOR

PRESSURIZING THE AIRCRAFT HYDRAULIC RESERVOIR USING EXTERNAL SOURCE AIR

### MODEL

HPT - 01

### ALTERNATIVE FOR

98D29003501000

98D29003501003

# FEATURES

---

- Requires external source of pressurized air
- Maximum inlet pressure 145 psi / 10 bar
- Outlet pressure adjustment 0 – 125 psi
  
- Air preparation unit with 5 micron filter
- Excellent water removal efficiency
- Inlet pressure gauge, accuracy 1,6% of full scale
- Outlet pressure gauge
  
- Ergonomic design
- Solid stainless steel frame with rigid and caster wheels
- Hooks for hose storage
- Inlet air hose 6 meter
- Outlet air hose 25 meter
- Adaptors for connecting tool to air pressure manifold or depressurization valve

# DIMENSIONS & WEIGHT

---

<b>LENGTH</b>	1270 cm
<b>WIDTH</b>	610 mm
<b>HEIGHT</b>	930 mm
<b>WEIGHT (empty)</b>	90 kg

# POSSIBLE OPTIONS

---

Other options are available upon request.



**HYCOM B.V.**

P.O. BOX 1079 | 7301 BH APELDOORN  
ANTILLEN 43 | 7333 PE APELDOORN

T +31 88 0597 200

E [INFO@HYCOM.NL](mailto:INFO@HYCOM.NL) | W [WWW.HYCOM.NL](http://WWW.HYCOM.NL)